

On page <sup>10</sup>~~9~~, the paragraph beginning at line <sup>20</sup>~~31~~ is changed as follows: ✓

Q2 "Next, at step 1005, the pressurizing unit 2 is operated, that is, the pressurizing actuators 22-1, 22-2 and 22-3 are individually driven by the feedback of the output signals of the pressure sensors 24-1, 24-2 and 24-3. In this case, each of the values of the output signals of the pressure sensors 24-1, 24-2 and 24-3 is brought close to a value which is one third of an initial total pressure such as 60 kgf, so that the pressure within each of the LCD panels P is made uniform."

On page <sup>11</sup>~~10~~, the paragraph beginning at line <sup>21</sup>~~31~~ is changed as follows: ✓

Q3 "Next, at step 1007, the pressurizing unit 2 is operated, that is, the pressurizing actuators 22-1, 22-2 and 22-3 are individually driven by the feedback of the output signals of the pressure sensors 24-1, 24-2 and 24-3. In this case, each of the values of the output signals of the pressure sensors 24-1, 24-2 and 24-3 is gradually increased to a value such as about 0.2 to 5 kg/cm<sup>2</sup>, so that the pressure within each of the LCD panels P is also made uniform. Simultaneously, since liquid crystal is poured from the liquid crystal injection openings OP of the LCD panels P, the wiping unit 3 is operated to wipe up the poured liquid crystal. While the wiping unit 3 is being operated four times, the pressurizing unit 2 is operated, so that the values of the output signals of the pressure sensors 24-1, 24-2 and 24-3 are gradually decreased to a value such as 1 kg/cm<sup>2</sup>, to stop the liquid crystal from being poured."

On page <sup>11</sup>~~10~~, the paragraph beginning at line <sup>26</sup>~~30~~ is changed as follows: ✓

Q4 "Next, at step 1009, the pressurizing unit 2 is operated, that is, the pressurizing actuators 22-1, 22-2 and 22-3 are individually driven by the feedback of the output signals of the pressure sensors 24-1, 24-2 and 24-3. In this case, each of the values of the output signals of the pressure

AMENDMENT UNDER 37 C.F.R. § 1.111

U.S. Application No. 09/772,955

Attorney Docket No. Q62734

*by  
Amend*

sensors 24-1, 24-2 and 24-3 is gradually decreased to zero, so that the pressure within each of the

LCD panels P is also made uniform. Thus, the liquid crystal injection openings OP of the LCD

panels P are completely sealed."

---